

AUSTRALIA
NEW ZEALAND
ASIA

The advertisement features a dark blue background. On the left is a red octagonal stop sign with the word "STOP" in bold black letters. To the right, the text "DON'T RE-USE THAT WORN LANTERN RING!" is written in large, white, bold, sans-serif capital letters. Below this, in smaller white text, it says "Bring your flushing capabilities back to new with a UNIVERSAL SEAL CAGE LANTERN RING (U.S. & Canadian Patent Nos. 4,498,681 and 1,271,788)". At the bottom center is a white, C-shaped lantern ring with a textured, segmented surface.

- Manufactured from Pure Teflon for chemical resistance
- Cuts and installs just like packing
- A few sizes will cover all your needs
- Up to 60% savings over O.E.M. part cost
- Greatly reduces inventory dollars – No more need to stock individual lantern rings
- Eliminate shutting down flush flow from packing extrusion
- Buy your sizes today and DO IT RIGHT!!!

Universal Seal Cage Lantern Ring

Operating Considerations:

Maximum Temperature: 260°C
PH: 0 - 14

Available sizes:

Size	Width	Roll length	App. Weight per roll
¼" (6.35mm)	3/8" (9.5mm)	1.219 metres	0.161 kg
5/16" (8mm)	7/16" (11mm)	1.219 metres	0.188 kg
3/8" (9.5mm)	½" (12.7mm)	1.219 metres	0.260 kg
7/16" (11mm)	9/16" (14.2mm)	1.219 metres	0.340 kg
½" (12.7mm)	5/8" (15.87mm)	1.219 metres	0.432 kg
9/16" (14.2mm)	11/16" (17.46 mm)	1.219 metres	0.532 kg
5/8" (15.87mm)	¾" (19mm)	1.219 metres	0.650 kg
¾" (19mm)	7/8" (22.2mm)	1.219 metres	0.905 kg
¾" (19mm)	1" (25.4 mm)	1.219 metres	
1" (25.4 mm)	1" (25.4 mm)	1.219 metres	

Other sizes available on request

Klinger Limited, 38 Mc Dowell Street, Welshpool, WA, 6106.

Telephone : (8) 92511600. Fax : (8) 93509286.

For further advice please contact: technical_service@klinger.com.au

Web page: www.klinger.com.au